

Batterie	Japan Code	Kapazität (Ah)	Max. Länge (mm)	Max Breite (mm)	Max Kastenhöhe (mm)	Schaltung Schema	Merkmale
----------	------------	----------------	-----------------	-----------------	---------------------	------------------	----------

6 Volt

	6N2-2A-1	2	70	47	96		MK
	6N2-2A-4	2	70	47	96		MK
	6N2A-2C-3	2	70	47	106		MK
	6N2-2D	2	70	47	103		MK
	6N4-2A	4	71	71	96		MK
	6N4-2A-3	4	71	71	96		MK
	6N4-2A-4	4	71	71	96		MK
	6N4-2A-5	4	71	71	96		MK
	6N4-2A-7	4	71	71	96		MK
	6N4C-1B	4	71	71	105		MK
MI00413	6N4A-4D	4	58	62	131		MK
	6N4B-2A	4	102	48	96		MK
MI00412	6N4B-2A-3	4	100	47	96		MK
	6N6-1B	6	99	57	121		MK
MI00611	6N6-3B	6	99	57	107	50	
	6N6-3B-1	6	99	57	111	50	
	6N6-1D	6	99	57	111	50	MK
	6N6-1D-2	6	99	57	107	50	MK
MI00714	B39-6	7	126	48	126	20	
MI00811	B49-6	8	91	83	161	21	
MI00800	6YB8L-B	8	121	71	95	50	
MI00812	3MO1	8	91	83	161	20	HGI
	6N11-2D	11	150	70	101	21	
M01214	6N11A-1B	11	122	62	132	20	
	B54-6	12	156	57	116	21	
MI01225	6N12A-2D (B54-6A)	12	156	57	116	21	
	B38-6A	13	119	83	161	20	

12 Volt

	12N5-3B	5	121	61	131	50	
MI50611	12N5,5-3B	5,5	138	61	131	50	
MI50613	12N5,5-4B	5,5	138	61	131	51	
	12N5,5-4A	5,5	138	61	131	51	
	12N5,5A-3B	5,5	103	90	114	50	
	12N7-3B	7	137	76	135	50	
	12N7-4A	7	137	76	135	51	
	12N7B-3A	7	151	61	131	50	
	12N7-4B	7	137	76	135	51	
	12N9-3A	9	138	77	141	50	
	12N9-3B	9	138	77	141	50	
	12N9-4B-1	9	138	77	141	51	
	12N10-3B	10	136	91	146	50	
	12N11-3A-1	11	136	91	156	50	
	12N12A-4A-1	12	136	82	162	51	
	12N14-3A	14	136	91	168	50	
	12N18-3	18	206	91	164	50	
	12N24-3A	24	186	126	177	50	

Batterie	Japan Code	Kapazität (Ah)	Max. Länge (mm)	Max Breite (mm)	Max Kastenhöhe (mm)	Schaltung Schema	Merkmale
----------	------------	----------------	-----------------	-----------------	---------------------	------------------	----------

12 Volt Hochleistungs - Batterien
CB ist wie YB

	YB2,5L-C-2	2,5	81	71	106	50	
MI50312	CB3L-A	3	99	57	111	50	
MI50313	CB3L-B	3	99	57	111	50	
MI50411	CB4L-B	4	121	71	93	50	
MI50512	CB5L-B	5	121	61	131	50	
MI50712	CB7L-B	8	137	76	134	50	
MI50811	CB7C-A	8	130	90	114	50	
MI50813	CB7-A	8	137	76	134	51	
MI50914	CB9-B	9	137	76	140	51	
MI50915	CB9L-B	9	137	76	140	50	
	CB9L-A2	9	137	76	140	50	
MI51111	CB10A-A2	11	135	90	155	51	
MI51112	CB10L-A2	11	136	91	146	50	
M51113	CB10L-B2	11	136	91	146	50	
MI51211	CB12A-A	12	135	81	161	51	
MI51212	CB12B-B2	12	161	91	132	51	
MI51213	CB12AL-A2	12	135	81	161	50	
MI51215	CB12A-B	12	135	81	161	51	
MI51411	CB14L-A2	14	135	91	167	50	
MI51412	CB14-A2	14	135	91	167	51	
MI51413	CB14L-B2	14	135	91	167	50	
MI51414	CB14-B2	14	135	91	167	51	
	YB14L-A1	14	136	91	168	50	
	SYB14L-A2	14	136	91	168	50	MS
	SYB14L-B2	14	136	91	168	50	MS
MI51615	CB16B-A	16	162	92	162	51	
MI51616	CB16AL-A2	16	205	71	164	50	
MI51617	HCB16A-A	16	151	91	182	51	
MI51814	BMW ohne ABS	18	186	81	170	50	
MI51815	CB18L-A	18	182	92	164	50	
MI51816	CB18-A	18	182	92	164	51	
	YB16CL-B	19	176	101	175	50	
MI51911	CB16L-B	19	176	101	156	50	
MI51912	CB16-B	19	176	101	156	51	
MI52012	C50-N18L-A	20	206	91	164	50	
	Y50-N18L-A3	20	206	91	166	50	
	SY50-N18L-AT	20	205	90	162	50	MS
S53030	53030	30	187	128	165	50	
S53034	53034	30	187	128	165	51	
	YB30L-B	30	168	132	176	50	
	YHD-12	32	207	132	167	50	

12 Volt AGM Motorradbatterien

	YT4B-BS	2,3	113	38	85,5	50	
MI50314	YTX4L-BS	3	114	71	86	50	

Batterie	Japan Code	Kapazität (Ah)	Max. Länge (mm)	Max Breite (mm)	Max Kastenhöhe (mm)	Schaltung Schema	Merkmale
MI50412	YTX5L-BS	4	114	71	106	50	
MI50614	YTX7L-BS	6	114	71	131	50	
MI50615	YTX7A-BS	6	150	87	94	51	
MI50812	YTX9-BS	8	150	87	105	51	
MI51012	YTX12-BS	10	150	87	132	51	
MI51013	YTX12A-BS	10	150	87	105	51	
MI51214	YTX14-BS	12	150	87	147	51	
MI81401	YTX14AH-BS	12	134	89	166	51	
MI81500	YTX15L-BS	13	175	87	130	50	
MI81501	YTX15-BS	13	175	87	130	51	
MI81600	YTX16-BS	14	150	87	161	51	
MI81601	YTX16-BS1	14	150	87	161	51	
MI82000	YTX20L-BS	18	175	87	155	50	
MI82001	YTX20-BS	18	175	87	155	51	
MI82002	YTX20CH-BS	18	150	87	161	51	
MI82003	YTX20HL-BS	20	175	87	155	50	
MI82004	YTX20H-BS	20	175	87	155	51	
MI82400	YTX24HL-BS	21	205	87	162	50	
MI85000	YTX50-BS	21	205	87	161	51	
MI85001	YTX50L-BS	21	205	87	161	50	
MI83000	YIX30L-BS	30	166	126	175	50	

HVT Motorradbatterien (spez. für Harley)

MIHVT-01	YTX20L-BS	18	176	87,5	155	50	
MIHVT-02	YIX30L-BS	30	169	131	174	50	
MIHVT-03	YTX14L-BS	12	105	87	145	50	
MIHVT-04	CB16L-B	19	175	100	157	50	
MIHVT-05	CB16-B	19	175	100	157	51	
MIHVT-06	YTX24HL-BS	22	205	90	163	50	
MIHVT-07	CHD4-12	28	205	130	165	51	
MIHVT-08	YTX14-BS	12	150	87	145	51	
MIHVT-09	YB7-A	7	137	76	134	51	
MIHVT-10	CB2-6	6 Volt 22 Ah	115	100	214	51	
MISLA12-20	519 13	20	180	78	172	50	

12 Volt

GEL Motorradbatterien

MIGEL12-4A-BS	YTR4A-BS	2,5	113	48	85	Steckkontakt	
MIGEL12-4L-BS	YTX4L-BS	3	114	69	87	50	

Batterie	Japan Code	Kapazität (Ah)	Max. Länge (mm)	Max Breite (mm)	Max Kastenhöhe (mm)	Schaltung Schema	Merkmale
MIGEL12-5L-BS	YTX5L-BS	4	114	69	109	50	
MIGEL12-5ZS	YTZ5-S	4	113	70	85	50	
MIGEL12-4L-B	YB4L-B	5	120	71	92	50	
MIGEL12-6ZS	YTZ6-S	5	113	70	105	50	
MIGEL12-7A-BS	YTX7A-BS	6	151	87	94	51	
MIGEL12-7B-4	YT7B-4	6	150	65	92	51	
MIGEL12-7L-BS	YTX7L-BS	6	114	69	135	50	
MIGEL12-7Z-S	YTZ7-S	6	113	70	105	50	
MIGEL12-9B-4	YT9B-4	8	150	65	102	51	
MIGEL12-9-BS	YTX9-BS	8	151	87	107	51	
MIGEL12-10B-4	YTZ10-S	8,5	150	87	96	51	
MIGEL12-9-4B-1	12N9-4B1	9	136	76	139	51	
MIGEL12-12A-BS	YTX12A-BS	10	150	87	106	51	
MIGEL12-12B-4	YT12B-4	10	150	69	130	51	
MIGEL12-12-BS	YTX12-BS	10	151	87	133	51	
MIGEL12-12Z-S	YTZ12-S	11	150	87	109	51	
MIGEL12-14ZS	YTZ14-S	11,5	150	87	110	51	
MIGEL12-12A-4A1	12N12A-4A-1	12	134	80	161	51	
MIGEL12-12AL-A	YB12AL-A	12	134	80	161	50	
MIGEL12-14B-4	YT14B-4	12	150	69	145	51	
MIGEL12-14-BS	YTX14-BS	12	151	87	145	51	
MIGEL12-14L-A2	YB14L-A2	14	134	89	160	50	
MIGEL12-16AL-A2	YB16AL-A2	16	205	70	162	50	
MIGEL12-20-BS	YTX20-BS	18	175	87	155	51	
MIGEL12-20L-BS	YTX20L-BS	18	175	87	155	50	
MIGEL12-16-B	YB16-B	19	175	100	156	51	
MIGEL12-16L-B	YB16L-B	19	175	100	156	50	
MIGEL12-N50-18L-A	Y50-N18L-A	19	205	90	160	50	
MIGEL51913	BMW mit ABS	21	183	78	171	50	
MIGEL53030	53030	30	187	130	170	50	
MIGEL53034	53034	30	187	130	170	51	